

Instant boiling and chilled filtered water



“ The development of a more rapid business cycle, along with a greater recognition of our environmental responsibility has created the demand for more efficiency.”



XL Levered Tap pictured on optional font

—Lowest Energy Consumption

Superior insulation is critical to the sustainable performance of any integrated boiling system. The Billi Eco utilizes Billi's unique high performance Thermostore™ technology and insulation materials which operate at a level of efficiency which exceeds 50 times that of a traditional hot water tank. In addition the Standby Mode will ensure after a set period of non-usage the unit will power down to prevent excess energy consumption.

—Unique Eco-Intelligence™ Technology

The Billi Eco incorporates Eco-Intelligence technology which is a self learning timer allowing the unit to only operate when required. The self learning timer monitors daily usage patterns and even recognises evening and weekend changes in routine to effectively minimise energy consumption.

—Australia's smallest underbench footprint

With dimensions of just 340mm high by 180mm wide by 500mm deep, this under bench unit is designed to maximise available space under the sink.

—No cupboard ventilation required

The Billi Eco is the only aircooled unit available that does not require ventilation.

—Safety First

Billi's SplashFree boiling water delivery means that the water flow is electronically varied, slowing momentarily to eliminate splashing as the water first enters the cup. All Billi dispensers are supplied standard with a safety switch.

—Adjustable chilled temperature

A simple adjustable control knob allows the chilled water temperature to be raised to 15 C or lowered to 6 C for perfectly chilled, refreshing drinks, with your required temperature being quickly reached and maintained

—New unprecedented tap range.

Billi now offering a choice of 4 tap styles.

—Australian designed, manufactured and owned.



Optional XT Touch Tap



Optional XR Remote Tap



Specifications and guide to model selection

Product Code	Model	Initial cup delivery suggested no. of persons	Boiling water delivery cups per hour	Chilled water delivery cups per hour	Current draw amps	Height mm	Width mm	Depth mm
901000	Eco	10	90	60	10	340	180	500

Water supply

A single 15mm (1/2") stop-tap with a male thread should be installed in an easily accessible position. Water supply must be microbiologically safe to drink, with a minimum dynamic water pressure of 250kPa and a maximum water pressure of 500kPa. Where water pressure is over 500kPa a PLV must be fitted. Billi recommends PLV's with anti hammer properties.

Power supply

The Billi Eco requires a standard 10 amp power outlet. It is supplied with a 1 metre flex cord and plug.

Warranty

All components of the Billi units are covered by a 24 month warranty. Filter cartridges are a consumable and are not covered by warranty, as water conditions and usage vary.

Certifications

Every Billi drinking water appliance is manufactured under a certified quality control system. The Billi Eco has been tested and complies with all required standards including: Watermark Licence Number 21525; Tested to; AS3498 and AS/NZS4020; Victorian Electrical Safety Act 1998 Approval Number CS100600V, AS/NZS ISO 9002; AS1428 Accessibility Design Requirements; Section J6 of the BCA; Certificate Number QEC 11627; C-Tick approved.

Technical Advice

Contact Billi Pty Ltd on 1300 300 316

Billi Pty Ltd
42 Lucknow Crescent
Thomastown Victoria 3074 Australia
Telephone +613 9469 0400
Facsimile +613 9649 0400
Website www.billi.com.au

As Billi Pty Ltd has a policy of continual improvement, all details are subject to change without notice. All goods sold are subject to our standard terms and conditions.

Filtration

Billi's premium filters ensure that health threatening pollutants and impurities such as sediment, chemicals, heavy metals, chlorine and pesticides are safely removed leaving you with refreshingly clean drinking water. All Billi cartridges are certified by global public safety agency NSF International*. Filter changes are made simple by our swing-change system and replacement cartridges are available online at www.billi.com.au. Optional sub micron and premium submicron filters are available.

Options and accessories

- **Dispenser Styles:** The Billi Eco & Quadra models are supplied standard with the XL Levered tap pictured below. Style options are the XT Touch Tap, XR Remote Tap and the QL Quadra Levered Tap.
- **Dispenser Finishes:** Standard finish for the Dispenser is Bright Chrome. Optional finish— Brushed Chrome or Black Chrome.
- **Billi Font:** Allows the dispenser to be located away from sink areas. Finished in polished Stainless Steel, optional brushed or black chrome finish available.
- **Dispenser Riser:** 70mm dispenser extension - supplied standard with the Billi Font.
- **Tubing Extension Kit:** Allows the dispenser to be offset from the under bench unit by up to 2 metres.

1 cup = 170ml. Based on the initial number of cups of boiling water immediately available, drawn one cup every 10 seconds. Consideration may be needed for usage patterns and draw-off methods.

Preferred installation layout

